



HydroTap G5 BCS60 Classic Plus Chrome

Boiling Chilled Sparkling

 **Finish:** Chrome

Product code: H55762Z00AU

Capacity: Commercial

Zip HydroTap Classic Plus Boiling, Chilled, Sparkling, Filtered water tap features simple, intuitive controls including continuous flow to fill bottles, Boiling water safety lock, and antimicrobial protection impregnated within the new Classic Plus touch-pad for enhanced hygiene. The water system features a single under bench command centre including full colour interactive touch screen display with pin code protection and customisable settings including 2 boiling water safety modes, 3 energy saving modes including ON/OFF timers and sensor activated 'sleep when it's dark', 'Quiet' mode with automated intelligent fan speed adjustment, antimicrobial protection impregnated into key water paths for enhanced hygiene, 100% water efficient air cooled technology, 0.2 micron water filtration, and a refillable CO2 cylinder. Easy to install integrated ventilation tray included.

Specifications

Product name	HydroTap G5 BCS60 Classic Plus Chrome
Product code	H55762Z00AU
Filtered water type	BCS
Product approvals	WaterMark, RCM, ARC
Warranty	5 years (appliance warranty 36 months plus additional 24 months tank warranty)

Capacity, weight & dimensions

Number of people	41-60
Boiling cups per hour	160
Combined chilled and sparkling cups per hour	175

Plumbing

Water supply requirements	Cold
Water connection	1/2" BSP (G1/2)
Water valves	Integrated 500kPa Pressure limiting valve and Dual Check Valve
Water pressure	Min 250kPa - Max 700kPa

Electrical

Power rating	2.15kW 220-240V 50Hz
Power supply	1 × 10 Amp socket outlet

Tap design

Tap	Zip HydroTap CLASSIC PLUS Tap (Chrome)
HydroTap style	Classic Plus
Finish	Chrome

Command centre

Dimensions

W395mm x D487mm x H333mm

Installation

Installation requirements

1. Installation and connection of your Zip HydroTap must be carried out by a qualified person, observing national and local regulations.
2. You will require suitable mains electrical and drinking water connections, plus waste water drainage all within 1.5 metres of the product.
3. **Discrete cabinetry cut outs are required for airflow. 40mm minimum clearance on cupboard base overhang required otherwise alternative installation options are available.**
4. Installation on most bench tops is straightforward however some stone bench tops may require a specialised cutting service.
5. If you live in a hard water area, we recommend installation of a Zip scale filtration kit.
6. Installation by Zip Professional Service can be arranged with a phone call or through www.zipwater.com/book-service-visit

Files

Installation Layout 3D (DWG)

Installation Layout 3D (DWG)

Installation Layout (PDF)

Ventilation requirements Contact your local service provider if ventilation is not suitable

Option 1. Cupboard with 40mm min overhang

40mm min

50mm min clearance beside inlet

100mm min clearance

Air inlet grille cut-out

Air exhaust cut-out

min. 40

325

350

Option 2. Cupboard with less than 40mm overhang

50mm min clearance beside inlet

Floor mounting plate cut-out

Air exhaust cut-out

40

350

60

285

Tap Positioning

Position the Tap to dispense into the sink. Alternatively, mount on a Font, available as an accessory.

Classic Plus tap

Raised Font with Extension (optional accessory)

4mm buffer pad air space

Clearance Envelope

Clearance Envelope

A minimum overhang or kickboard height is required for ventilation. Refer to the installation instructions.

500

500

50 min.

395

333

487

Air inlet grille

CO₂ gas cylinder

IEC Flex & Plug 230-240V, 10A, 50Hz power outlet

Mains cold water isolation valve (not supplied)

HydroTap Tap options

Classic Plus

116

216

126

Ø46

Ø35mm hole required

Classic

116

208

126

Ø46

Ø35mm hole required

Elite Plus

112

221

134

Ø46

Ø35mm hole required

Touch-Free Wave

100mm clearance envelope is required.

116

214

126

Ø46

Ø35mm hole required

100

Font options

Raised Font with 135mm Extension part no. 95258

116

260

351

Ø46

116

200

268

Font with 135mm Extension part no. 90915

116

260

351

Ø46

104

6

Ø219

Cutting detail

Ø10 for M6 stud

Ø86 hole for bowl

Ø35 hole for tap

152

116

164

Cutting detail

Ø108 hole for bowl

Ø35 hole for tap

Ø10 for M6 stud

60

104

Ø219

HydroTap G5 BCS60

shown with Classic Plus tap and Raised Font (optional accessory)

SCALE 1:5

ALL DIMENSIONS IN MM UNLESS OTHERWISE SPECIFIED. INSTALLATION DIAGRAMS ARE FOR ILLUSTRATIVE PURPOSES ONLY. HOSES ARE NOT SHOWN TO SCALE AND CANNOT BE LENGTHENED.

BIM files



↓ ArchiCAD Swift
Globals Library
(LCF)



↓ ArchiCAD Zip Water
Library (LCF)



↓ Revit Project File
(RFA)



↓ Revit Virtual
Showroom (RVT)

↓ Download all

Certifications



Environment
ISO 14001



Health & Safety
AS/NZS 4801



Quality
ISO 9001



↓ ARC (PDF)



↓ Environment ISO
(PDF)



↓ Environmental
Product Declaration
Brochure (PDF)



↓ Filter performance
(PDF)



↓ Health & Safety
(PDF)



↓ HydroTap Clean
SDS (PDF)



↓ Quality ISO (PDF)

Manuals & brochures



↓ Brochure (PDF)



↓ CO₂ MSDS (PDF)



↓ Instruction manual (PDF)



↓ Quick guide (PDF)



↓ Tap operation label (PDF)



↓ User manual (PDF)

↓ Download all